

Use

- › ACE Energy AGM batteries are specially designed for frequent charging and discharging.
- › They are suitable for storage of renewable solar and wind energy, mobility and medical equipment, cable TV, etc.



Specifications

		AGM12-95	AGM12-100
	Reference	22611-01VLU	22612-01VRU
Electrical Specifications	Rated Voltage	12 V	12 V
	Nominal Capacity (20HR)	95 Ah	105 Ah
	Nominal Capacity (10HR)	-	100 Ah
	Internal Resistance	≤3.5 mΩ	≤5 mΩ
	Max. Discharge Current (5s)	1080 A	1000 A
	Continuous discharge current	100A	100A
	Maximum load current	23 A	30 A
	End-of-charge voltage	13.5V – 13.8 V @25°C	13.5V – 13.8 V @25°C
Environment	Charge Temperature	-30°C à 60°C	0°C à 40°C
	Discharge Temperature	-30°C à 60°C	-15°C à 50°C
	Storage Temperature	-30°C à 40°C	-15°C à 40°C
Mechanical Specifications	Container Material	PP	ABS
	Dimensions (L x W x H)	35.3 x 17.5 x 19 cm	33 x 17.3 x 22 cm
	Weight	26.5kg	28 kg
	Terminal	SAE	M8