BCV-20120



Description

- > With an integrated LiFePO4 battery, the E-Box offers you an all-in-one solution for your vehicle's energy autonomy.
- Specially designed to fit under the passenger seat, this battery covers all the electrical needs of the adapted cell while taking up minimal space.
- As an optional feature, you can also integrate the 12V distribution panel.



BCV-15120

Features

> Fully integrated

A single box containing the LiFePO₄ battery, the DC/DC charger, the AC/DC charger, the MPPT solar charge controller and the DC/AC converter.

- More powerful and longer-lasting Provides twice as much power as a lead battery while maintaining a high energy capacity. Up to 2500 cycles at 0.5 C charge and discharge.
- Wide temperature range
 TOperating temperature ranging from -20 °C to 60 °C.
- > Power supply prioritisation
 Thanks to the Box ACE Energy's builtin power prioritisation board, you can
 automatically manage the 230V_{AC} power
 supply when the vehicle is connected to
 the power supply via the external outlet.
- Communication
 Control the battery charging level and status via a dedicated mobile app.

| AC= | 100Ah batteries version 1.0.0 |
|---------------------------|----------------------------------|
| 75 | 5 % |
| 13.37 V Voltage | + 10.3 A Current |



| | Reference | 10310-1500W | 10310-2000W |
|-----------------------|---------------------------|-------------------------------|-------------|
| Technical features | Nominal voltage 12.8V | | V |
| | Nominal capacity 120Ah | | λh |
| | Full battery voltage 14.6 | | iV . |
| | Rated power | 1530Wh | |
| | Internal resistance | ≤30mΩ | |
| | Charge current | ≤100A | |
| | Discharge current | 150A | 200A |
| | Peak current | 300A | 400A |
| | Useful life | ≥2500 cycles | |
| | Self-discharge | <3% | |
| DC-DC charger | Applicable voltage | 12-16V | |
| | Charge current | 50 to 70A (dedicated line) | |
| | Automatic D+ detection | Optional | |
| AC-DC charger | Applicable voltage | 230-240V _{AC} / 50Hz | |
| Charge current | | 20A | |
| Solar charger | Applicable voltage | ≤80V | |
| | Charge current | 20A | |
| | Maximum power | 290W | |
| DC-AC converter | Output voltage | 230-240V _{AC} / 50Hz | |
| | Rated power | 1500W | 2000W |
| | Peak power | 3000W | 4000W |
| Mechanic | Materials | ABS + PEHD | |
| | Dimensions | 350 x 370 x 210 mm | |
| | Weight | 25kg | |
| Communication | Bluetooth 4.2 | Android and iOS mobile app | |







Auxiliary battery

Increase your capacity to 240Ah with auxiliary battery Ref. ACE-AUX120

